

**Technical Data Sheet**

**Compression Packing**


**Flexitallic 26L**

Flexitallic 26L compression packing, is a soft packing constructed by X-braiding pure PTFE yarn impregnated with PTFE dispersion and silicon-free lubricant.



Flexitallic 26L can be used in rotary and reciprocating applications handling most chemical media. It is especially used in applications involving concentrated acids or where non-contamination of the product is required. The relatively soft and conformable nature of Flexitallic 26L enables sealing to be achieved with minimum gland pressure. Typical sealing applications include aggressive chemicals, foodstuffs and pharmaceuticals.

- Materials of construction: Pure PTFE yarn impregnated with silicon- free lubricants.
- Colour: White.
- Typical applications: Pumps, Mixers and Control Valves.
- FDA compliant.



Temperature: Maximum	250 °C (482 °F)
Minimum	-100 °C (-148 °F)
Pressure: Maximum	Rotating – 7 MPa (1015 psi) Valve – 20 MPa (2900 psi) Reciprocating – 15 MPa (2174 psi)
Speed: Maximum	Rotating – 8 m/s (1575 fpm) Valve – 2 m/s (394 fpm) Reciprocating – 2 m/s (394 fpm)
pH Range	0 – 14
Standard Sizes (mm sq.)	3.2, 5.0 - 20m spools. 6.0, 6.5, 8.0, 9.5, 10.0, 11.0, 12.0, 12.5, 14.0, 14.5, 16.0, 18.0, 19.0, 22.0, 25.0 – 8m spools

Care should be taken in selecting the most suitable quality for each application. Advice is available, but final responsibility remains with the customer.

**Web: [www.epdm.co.uk](http://www.epdm.co.uk)**

**E-Mail: [Sales@epdm.co.uk](mailto:Sales@epdm.co.uk)**

**Contact**

Telephone: +44 (0)1625 573971  
 FAX: +44 (0)1625 573250  
 Munsch & Co/PTM Ltd  
 Units AG2/3 Clarence Mill  
 Clarence Road, Bollington  
 Macclesfield, Cheshire  
 SK10 5JZ  
 United Kingdom



Certificate Number: 14352  
 ISO 9001

